



## High Precision GPS/GNSS/L1/L2/L5/L6 Flexible Polymer Adhesive Antenna

### Description

Passive Multiband GNSS Antenna That Combines High Precision, Flexibility For High Performance and Reliability

The 2JF0201P is a passive multiband constellation antenna, ideal for applications using high precision GNSS L1, L2, L5, and L6 bands. It can receive GPS, GLONASS, BeiDou, Galileo, QZSS, SBAS, and IRNSS signals, making it ideal for multiple applications including land survey, transportation and autonomous vehicles. This antenna allows the user to achieve higher location accuracy, as well as stability of position tracking in urban environments, mountainous or rough terrain.

This high-performance antenna is designed to operate on low power consumption without compromising its high efficiency of up to 79.9% across all bands within 1176 – 1606 MHz. Efficiency is 75% in L5 and 76.2% in L2 band, making it one of the most reliable solutions on the market. The 2JF0201P has excellent performance and its design achieves a 4.9 dBi GNSS passive peak gain with an excellent broad axial ratio, which makes it resilient to multipath rejection and excellent phase center stability.

Suggested applications include:

Installation / Environmental

The 2JF0201P is a flexible polymer antenna manufactured without any hazardous materials, and it is both REACH and RoHS compliant. Exceptional durability in temperatures ranging between -40C and 85C. The combination of flexible polymer material, thin size design, and self-adhesive mounting make the integration process extremely simple. The 2JF0201P comes with a standard U. FL connector. This antenna is fully customizable with a large selection of connector types, cable lengths, and cable types. This is ground plane independent making it highly suitable to be installed on any metallic surface.

Technologies GPS/Glonass/BeiDou/QZSS/Galileo/IRNSS/SBAS/L1L2L5L6

Bandwidth (MHz) 1176-1208, 1227-1246, 1268-1279, 1561-1606

Bands L5, L2, L6, L1

Frequency 1176.45, 1207.14 / 1227.6, 1246.00 / 1268.52, 1278.75 / 1561.09, 1575.42, 1602.00

Standards GPS(L5), BeiDou(B2a, B2b), QZSS(L5), Galileo(E5a), IRNSS(L5) / GPS(L2C), GLONASS(L2OF), QZSS(L2C) / GPS(L6), BeiDou(B3), QZSS(L6), Galileo(E6) / GPS(L1C), GLONAS(L1OF), BeiDou(B1), QZSS(L1C), Galileo(E1), SBAS (L1)

Return Loss (dB) ~-12.8, ~-16.6, ~-9.3, ~-21.8

VSWR ~1.6:1, ~1.4:1, ~2.1:1, ~1.2:1

Efficiency (%) ~75.0, ~76.2, ~74.2, ~79.9  
Passive Peak Gain (dBi) ~3.2, ~3.1, ~2.9, ~4.9  
Average Gain (dB) ~-1.3, ~-1.2, ~-1.3, ~-1.0  
Impedance (Ohm) 50  
Radiation Pattern Omni-Directional  
Polarization Linear  
Max. Input Power (W) 25

**Date Created**

June 10, 2022

**Author**

nick